



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.3876$   $y=0.3816$   $u'=0.2279$   $v'=0.5047$

CCT=3848K(Duv=0.0002) Dominant WL:Ld =579.5nm Purity=30.8%

Peak WL:Lp=454.0nm FWHM=21.2nm

Render Index:Ra=83.6 Render Index:AvgR =77.1

|        |        |        |        |        |        |        |        |
|--------|--------|--------|--------|--------|--------|--------|--------|
| R1 =82 | R2 =91 | R3 =96 | R4 =81 | R5 =82 | R6 =86 | R7 =86 |        |
| R8 =65 | R9 =14 | R10=77 | R11=79 | R12=60 | R13=85 | R14=98 | R15=77 |

### Photometric & Radiometric Parameters

Flux=663.4 lm Eff.:59.59 lm/W Fe=2.027 W

### Electrical parameters

V=24 V I=0.4608 A P=11.05 W PF=1.000 F=0.00 Hz

Status: Integral T = 276 ms Ip = 46423 (71%)

Test Mode: Fast Test; Sensitivity = High; Tecool: ON

Model:C-SFR-F22B-VB-D24CC-W4000-108-2835-1M

Test By:SHAN

Temperature:25.3Deg

Manufacturer:

Assessor:

Date:2018-06-15 13:57:20

Humidity:63.0%

Remarks:

Standard: